

8. OEM facility available.

# Specifications:

lighting products.

Model	CR-MD3-10W-SML	CR-MD6-20W-SML
Power	10W	20W
LED	COB	
LED Source	BRIDGELUX	
System Luminous	90~100LM/W	
Color Temperature Available	3000K (WW)/4000K (NW)/5000	)K (DL)/6500K (CW)
Beam Angle	15°,24°	
Input Voltage	100~277VAC, (50/60Hz)	
Power Factor	≥0.9	
CRI	Ra≥70~80	
LED Driver	<b>LiFUd</b> Isolated (THD≤20%)	
SDCM	<3	
Working Temprature	-20°C ~ +50°C	
Humidity	10%~90%	
Housing Color	White / Black	
Material	Aluminium	
Size	D75xH120	D150xH160
Weight (approx)	1.2 Kg	2.0 Kg
Life @TJ=	50,000 hrs	

6. It emits very low heat thereby reducing the air-conditioning cost.

7. We offers a 5 years warranty. (3 Years parts replacement warranty and 2 Years services warranty).























# Linear Recessed/ Suspended Light

#### **Product Features**

- Energy Saving Technology.

  LED Linear Light saves energy, help the environment.


  LED Linear Light are the latest generation solution to replace conventional.
- High performance, high brightness, high efficiency.
   Creat L≡D Linear Light have unique structure for excellent heat dissipation. With Aluminium alloy.
   Low heat emission (low temperature) reduces the cost of air conditioning.
- Highly reliable isolated constant current driver, with high power factor & low
- THD % guarantees long life span of the lamp beads.

  CrestL=D Linear lights offer up to 85% saving in electricity cost compared to energy saver / halogen lamp / fluorescent lamps and are designed to last for longer period.
- Creat L=D Linear Light have special (optional) design with external driver for high temperature areas to improve Thermal Efficiency of product and increase its life expectancy.
- 10. Eco-Friendly, mercury free, lead free.11. 12/24VDC Model available, specially for Solar use.
- 12. Dimmable model (optional).
- 13. 5 years warranty. (3 Years Parts repalcement warranty and 2 Years services warranty) 14. OEM service available.

Model	CR-Q4-18W-LRL
Power	18W
LED	SMD
LED Source	BRIDGELUX
System Luminous	110~120LM/W
Color Temperature Available	3000K (WW)/4000K (NW)/5000K (DL)/6500K (CW)
Beam Angle	120°
Input Voltage	100~277VAC, (50/60Hz)
Power Factor	≥0.9
CRI	Ra≥70~80
LED Driver	LiFud Isolated (THD≤20%)
SDCM	<3
Working Temprature	-20°C ~ +50°C
Humidity	10%~90%
Housing Color	Black Finish
Material	Aluminium
Size	L1200xW50xH75
Weight (approx)	2.4 Kg
Life @Tj=	50.000 hrs







(Explosion view)



















# Track Light

#### **Product Features**

- CreatL=D Track Light has a smooth texture look.
- It's structure is compact and has good appearance.
- Creat L=D Track lights are compact, high efficiency and alternatives to conventional lighting & has excellent lighting performance.

  CreatL=D Track Lights are equipped with a durable,
- constant current output driver and its Die Cast Aluminium made housing increases the thermal efficiency.
- LED Track Lights are multipurpose, offer up to two third savings in electricity costs compared to halogen lamps.

  CreatL=D Offers eco-friendly, mercury free, lead free LED
- lighting products.

  Creat L=D Technology makes the light last more than 50,000 hours & offers up to 85% energy saving.
- Low heat emission (low temperature) reduces the cost of air
- conditioning.

  Creat LaD Lights are backed by 5 years warranty. (3 Years Parts Warranty and 2 Years service warranty)
- 10. OEM facility available.


	· · · · · · · · · · · · · · · · · · ·
Model	CR-PS5-35W-TRL
Power	35W
LED	COB
LED Source	BRIDGELUX
System Luminous	90~100LM/W
Color Temperature Available	3000K (WW)/4000K (NW)/5000K (DL)/6500K (CW)
Beam Angle	15°,24°,38°,60°
Input Voltage	100~277VAC, (50/60Hz)
Power Factor	≥0.9
CRI	Ra≥70~80
LED Driver	LiFud Isolated (THD≤20%)
Track connector	3 Wire
SDCM	<3
Working Temprature	-20°C ~ +50°C
Humidity	10%~90%
Housing Color	White / Black
Material	Aluminium
Size	D93xH115
Weight (approx)	950 gm
Life @Tj=	50,000 hrs



























#### **Product Features**

- 1. CrestL=D Pendant lights are a revolution to lighting technology.
- 2. Spreads light with a clear and focused beam of light enhancing the beauty of surrounding.
- 3. It has a compact well-designed structure, well suited for home & office environment.
- 4. Creat L≡D Pendant Lights are equipped with a durable, isolated constant current ≥0.9PF output driver.
- 5. Solid state, Instant Start LED energy saving Technology.
- 6. CrestL=D Technology makes the light last more than 50,000 hours & offers up to 85% energy saving.
- 7. CreatL=D Offers eco-friendly, mercury free, lead free LED ligh ng products.
- 8. It emits very low heat thereby reducing the air-conditioning cost.
- Creat L=D Lights are backed by 5 years warranty.
   3 Years Parts replacement warranty and 2 Years services warranty.
- 10. OEM facility available.

# Specifications:

Model	CR-JC50-48W-PL	CR-JC50-76W-PL
Power	48W	76W
LED	SMD	
LED Source	BRIDGELUX	
System Luminous	100~120 LM/W	
Color Temperature Available	3000K (WW)/4000K (NW)/5000	DK (DL)/6500K (CW)
Beam Angle	120 <sup>0</sup>	
Input Voltage	90~265VAC, 50/60Hz	
Power Factor	≥0.9	
CRI	Ra≥70~80	
LED Driver	<b>LiFud</b> Isolated (THD≤20%)	
SDCM	<3	
Working Temprature	-20°C ~ +50°C	
Humidity	10%~90%	
Protection Class	IP20	
Housing Color	Matt Grey	
Material	Aluminium	
Size	L1200xW55xH75	L1200xW55xH75
Weight (approx)	11.5 Kg	13.7 Kg
Life @TJ =	50,000 hrs	













Pendant / Hanging Light















#### **Product Features**

- CreatL=D Tri-Proof Light is a latest energy saving solution available in transparent & frosted PC cover.

  CreatL=D Tri-Proof Lights are multipurpose, well suited for home, commercial & office environment. It has a well-designed efficient thermal management system, made of Aluminum alloy fins and well known for high brightness, performance and efficiency.

  CreatL=D Tri-Proof Lights are equipped with an isolated, Low THD%, durable >0.9PF constant current output driver ensuring long life of lamp.

  Solid state, Instant Start LED energy saving Technology.

  CreatL=D Technology makes the light last more than 50,000 hours & offers up to 85% energy saving.

  Low h t emission (low temperature) reduces the cost of air conditioning.
- 5.

- conditioning. 'creatL=D offers eco-friendly, mercury free, lead free
- LED lighting products.
- 9. It emits very low heat thereby reducing the air-conditioning cost.10. Creat Lights are backed by 5 years warranty. (3 Years Parts Replacement warranty and 2 Years services warranty)
- 11. OEM facility available.

Model	CR-4-T22W-TPS
Power	22W
LED	SMD
LED Source	BRIDGELUX
System Luminous	130~140 LM/W
Color Temperature Available	3000K (WW)/4000K (NW)/5000K (DL)/6500K (CW)
Beam Angle	120°
Input Voltage	100~277VAC, 50/60Hz
Power Factor	≥0.9
CRI	Ra≥70~80
LED Driver	LiFud Isolated (THD≤20%)
SDCM	<3
Working Temprature	-20°C ~ +50°C
Humidity	10%~90%
Protection Class	IP66 (According IEC-EN-60958)
Housing Color	Matt Grey
Material	Aluminium
Size	L1200xW95xH80
Weight (approx)	2.5 Kg
Life OTJ =	50,000 hrs



























#### **Specifications:**


12. OEM facility available.

Model	CR-N6060-35W-PL
Power	35W
LED	SMD
LED Source	BRIDGELUX
System Luminous	90~100 LM/W
Color Temprature Available	3000K (WW)/4000K (NW)/5000K (DL)/6500K (CW)
Beam Angle	150⁰
Input Voltage	100~277 VAC, 50/60 Hz
Power Factor	≥0.9
CRI	Ra≥70~80
LED Driver	LiFud Isolated (THD≤20%)
SDCM	<3
Working Temprature	-20°C ~ +40°C
Humidity	10%~90%
Housing Color	Matt White Finish
Material	Iron Base + Aluminium Frame + PS Diffuser
Size	L595xW595xH30
Weight (approx)	
Life @Tj =	50,000 hrs

11. We offers 5 years warranty. (3 Years Parts replacement and 2 Years services warranty).



#### OPTIONAL PS DIFFUSER SHEET ONLY FOR Above SLIM PANAEL & PANELS


























#### **Product Features**


- 1. CreatL=D Slim Panel light is a latest energy saving solution for unique & stylish indoor lighting.
- 2. It is multipurpose, well suited for home & office environment.
- 3. It has a well-designed efficient thermal management system.
- 4. Made of Aluminum alloy and side lit reflector sheet for high brightness, performance and efficiency.
- 5. Solid state, Instant Start LED energy saving Technology.
- 6. LED technology makes the bulb last 50,000 hours.
- 7. It is eco-friendly, mercury free, lead free and does not contain any hazardous materials.
- 8. It emits very low heat thereby reducing the air-conditioning cost.
- 9. 12/24VDC Model available, specially for Solar use.
- 10. Dimmable model (optional).
- 11. We offers a 5 years warranty.
  (3 Years parts replacement warranty and 2 Years services warranty).
- 12. OEM facility available.

Model	CR-6060-35W-SPL
Power	35W
LED	SMD
LED Source	BRIDGELUX
System Luminous	90~100 LM/W
Color Temprature Available	3000K (WW)/4000K (NW)/5000K (DL)/6500K (CW)
Beam Angle	150 <sup>⁰</sup>
Input Voltage	90~265VAC, 50/60 Hz
Power Factor	≥0.9
CRI	Ra≥70~80
LED Driver	LiFud Isolated (THD≤20%)
SDCM	<3
Working Temprature	-20°C ~ +40°C
Humidity	10%~90%
Housing Color	Matt White Finish
Material	Iron Base + Aluminium Frame + PS Diffuser
Size	L600xW600xH13
Weight (approx)	4.9 Kg
Life @Tj=	50,000 hrs

























- 8. It emits very low heat thereby reducing the air-conditioning cost.
- Creat L=D Lights are backed by 5 years warranty.
   3 Years Parts replacement warranty and 2 Years services warranty.
- 10. OEM facility available.

Model	CR-HB5-50W-PL
Power	50W
LED	SMD
LED Source	BRIDGELUX
System Luminous	80~90 LM/W
Color Temperature Available	3000K (WW)/4000K (NW)/5000K (DL)/6500K (CW)
Beam Angle	60°,90°,120°
Input Voltage	100~277VAC, 50/60Hz
Power Factor	≥0.9
CRI	Ra≥70~80
LED Driver	LiFud Isolated (THD≤20%)
SDCM	<3
Working Temprature	-20°C ~ +50°C
Humidity	10%~90%
Protection Class	IP65
Housing Color	Matt Dark Grey
Material	Aluminium
Size	D455xH365
Weight (approx)	
Life @Tj =	50,000 hrs



















Beam Angle 120°



Linear / Suspendend
with Comb Light

#### **Product Features**

- Energy Saving Technology.
- LED Linear Light saves energy, help the environment.
- LED Linear Light are the latest generation solution to replace conventional fluorescent tubes.
- 4. High performance, high brightness, high efficiency.
- CreatL=D Linear Light have unique structure for excellent heat dissipation. With Aluminium alloy.

  6. Low heat emission (low temperature) reduces the cost of air conditioning.
- Highly reliable isolated constant current driver, with high power factor & low
- THD % guarantees long life span of the lamp beads.

  8. CreatL=D Lights offer up to 85% saving in electricity cost compared to energy saver / halogen lamp / fluorescent lamps and are designed to last for longer period.
- Creat L=D Linear Light have special (optional) design with external driver for high temperature areas to improve Thermal Efficiency of product and increase its life expectancy.
- 10. Eco-Friendly, mercury free, lead free.11. 12/24VDC Model available, specially for Solar use.
- 12. Dimmable model (optional).
- 13. 5 years warranty. (3 Years Parts repalcement warranty and 2 Years services warranty)
- 14. OEM service available.

Model	CR-H5-45W-LRL
Power	45W
LED	SMD
LED Source	BRIDGELUX
System Luminous	100~110 LM/W
Color Temperature Available	3000K (WW)/4000K (NW)/5000K (DL)/6500K (CW)
Beam Angle	120°
Input Voltage	100~277VAC, 50/60Hz
Power Factor	≥0.9
CRI	Ra≥70~80
LED Driver	LiFud Isolated (THD≤20%)
SDCM	<3
Working Temprature	-20°C ~ +50°C
Humidity	10%~90%
Protection Class	IP20
Housing Color	Black Finish
Material	Aluminium
Size	L1800xW50xH70
Weight (approx)	3.5 Kg
Life @T=	50,000 hrs

















